

Dimensionen

TIRE SIZE	RIM SIZE	TIRE DIMENSIONS		LOAD CAPACITY			WEIGHT (kg)
		Section width (mm)	O.D. (mm)	Load wheel (kg)	Steering wheel (kg)	Static (kg)	
4.00-8	3.00D-8	105	406	950	730	1100	10.0
5.00-8	3.00D-8	132	452	1415	1090	1645	16.0
15x4-8	3.00D-8	112	375	1040	800	1210	10.0
16x6-8	4.33R-8	155	410	1270	975	1470	15.0
18x7-8	4.33R-8	158	455	2145	1650	2490	20.0
6.00-9	4.00E-9	145	523	1885	1450	2190	27.0
21x8-9	6.00E-9	187	524	2755	2120	3200	35.0
6-50-10	5-00F-10	174	574	2340	1800	2720	37.0
23x9-10	6-50F-10	243	583	3160	2430	3670	46.0
7.00-12	5.00S-12	179	653	2920	2240	3380	49.0
8.25-12	5.00S-12	215	670	3445	2650	4000	65.0
27x10-12	8.00G-12	234	675	3900	3000	4530	70.0
5.50-15	4.50E-15	165	680	2430	1870	2825	40.0
6.00-15	4.50E-15	185	680	2430	1870	2825	42.0
7.00-15	5.50-15	187	731	3545	2725	4115	56.0
7.50-15	6.00-15	190	800	3900	3000	4530	69.0
7.50-16	6.00-16	190	800	3900	3000	4530	72.0
8.15-15	7.00-15	214	710	3445	2650	4000	64.0
8.25-15	6.50-15	217	810	4600	3540	5354	93.0
28x9-15	7.00-15	222	695	3445	2650	4000	67.0
250-15	7.00-15	222	695	3445	2650	4000	65.0
3.00-15	8.00-15	324	823	5735	4410	6660	125.0
9.00-20	7.00-20	230	992	6000	5000	6600	134.0
10.00-20	7.00-20	230	992	6000	5000	6600	134.0
11.00-20	7.50-20	240	1000	6540	5450	8230	165.0
11.00-20	8.00-20	255	1000	6540	5450	8230	175.0
12.00-20	8.00-20	270	1070	7500	6250	8250	210.0
12.00-20	10.00-20	352	1098	7800	6500	8970	230.0
14.00-24	10.00-24	405	1313	10800	9000	12420	410.0
14.00-25	11.25-25	405	1313	10800	9000	12420	415.0

Note : Click Tire of above sizes are available.



DIMENSIONS OF SOLID INDUSTRIAL TYRES		
Forklift type	Displayed As	Examples
Motor generated	B-d	600-9
Electrical	DxB-d	21x8-9

TREAD PATTERN



URS is a member of Registrar of Standards (Holdings) Ltd.
ISO 9001:2008

Europe Office
WHYRES
Wheels & Tyres
 Dieselstraße 4
 72770 Reutlingen

Tel: +49 (0) 7121/380361
 Fax: +49 (0) 7121/380362
 E-Mail: info@whyres.de